

MORE QUALIFIED ONE

A new pioneer in repairing machines of air conditioner

Certified ISO-9002

Automatic Operation

- Automatic Refrigerant Refill
- Automatic Air Purge
- Automatic Oil Drain
- Automatic LCD Light Control



Auto discharge function of non-condensed gas in internal tank.



Almost permanent usage, Reducing refrigerant gas waste, Easy to repair.



No need to oil check with using oil-less vacuum pump.



Prevent over pressure with equipping condenser.



Prevent disorder caused by bad connection with equipping, non-connect point relay.



If you supply external gas to this machine, you can use till up to the gas is totally burnt out without thank replacement.



Extend scale life with using an electronic scale shock buffer.



KOENG CO., LTD.

B-806, Twintower, 345-9 Gasan Dong,
Gumcheongu Seoul, Korea
Tel : +82 2 6292 6300 / +82 2 838 6300
Fax : +82 2 6292 6292 / +82 2 839 4700
Website : www.koeng.com
E-mail : export@koeng.com

MS 682



Features

- Recovery/ Recycle/ Vacuum/ Charge
- Electron balance protection system for impact absorption
- Large size dual condenser installation
- Operating method is easy progressive form display screen and membrane keyboard
- Fine digital Electron Balance(10g/50kg)
- Core type large size dry filter
- High temperature/ High pressure compressor for only refrigerant
- Station vacuum pump/ Full automatic injection function
- Automatic discharge function for waste oil
- Automatic refrigerant transfer and tank receipt
- Overpressure power prevention and inside protection system
- Refrigerant injection amount memory function for all models of car
- Multi Languages support
- 3" 1/2 inch large size gauge only for refrigerant(Made in USA)
- 16kg recovery tank
- 3000mm high pressure hose only for refrigerant
- Parker quick Adapter
- Charge function(option)

Specification

CLASS	SPECIFICATION	REMARKS
REFRIGERANT	HFC - R134a	CFC - R12 Order made
CONTROL	Micro controller	Adaptation of electronic scale, Sensor, solenoid.
DISPLAY	Graphics LCD	240*128
KEYBOARD	Membrane Type	22 Key
Press. GAUGE	3' 1/2 inch (93φ)	
SOLENOID	Exclusive use for high pressure refrigerant	Made in Korea
BLOCK	High precision process	Made in Korea
CONDENSER	DUAL Type	Made in Korea
QUICK ADAPTER	Manual Type	Made in USA
FILTER DRYER	33sq.IN	Core Type
LOADCELL	10g / 50kg	
COMPRESSOR	220V 4.0A	1/3 HP 50HZ
VACUUM PUMP	220V 3.0A	3CFM
TANK CAPACITY	12kg	Liquid Full - 18kg
CASE	High quality resin molding and Steel structure	Light Green/Dark Gray
USE TEMP	10 ? 45°C (Passed high temperature test)	Possible with low temperature injection
POWER	AC 220V / 60HZ	50Hz (Option)
WEIGHT	87kg	-
BASE SIZE	750*500*1080	-