

CUMMINS INJECTOR TESTER DNGT 205

DNGT 205

Specification



Drive motor	AC 3Ø 220V 5HP, 0-3000 RPM
F/O pump motor	AC 3Ø 220V 1.5KW 4P PUMP
F/O pump	Max. out put pressure 70 kg/ cm ² , 7.5 ℓ/Min
F/O tank capacity	38 ℓ
F/O heater	AC 1Ø 220V PT 1" 2.5KW
L/O pump motor	AC 3Ø 220V 0.4KW 4P, 7.5ℓ/Min. 16 kg/ cm ²
L/O tank capacity	32 ℓ
L/O heater	AC 1Ø 220V PT 1"? 1KW
CAM BOX operating device	Drive motor (CAM exchange type)
Measuring cylinder	500 cc
F/O cooling device	Solenoid automatic
F/O tank temperature controller	PT 100Ω couple, 0-999 °C, 2 output controller
L/O tank temperature controller	PT 100Ω couple, 0-999 °C, 1 output controller
F/O tank level alarm	Alarm system
L/O tank level alarm	Alarm system
Rotating meter	Rotary encoder, 0 ~ 9999,Digital display, Standard 10 50 RPM
Stroke meter	0 ~ 9999 button & indicator , Standard 50 stroke
F/O supplying pressure gauge	Ø110 x 15 kg/ cm ²
L/O supplying pressure gauge	Ø110 x 15 kg/ cm ²
Dimensions (mm)	1300 x 805 x 1450 (h)