

Soundproof -


# DIESEL GENERATOR

**BKS - 10000 / BKS - 13000**



## FEATURES

- Compact and Light Weight
- Designed for Safety
- Oil Alert System
- Quiet Operation
- Easy Operation

 **Koeng Co., Ltd.**

<http://www.koreaeng.co.kr>



# DIESEL GENERATOR

## FEATURES

### 1. Compact and Light Weight

The BKS-10000 & 13000 boat an excellent, portable and compact design for the perfect on-site operations. As it is easy to put in a van or light truck, you can work whenever you want.

### 2. Designed for Safety

When engine oil falls to a very low level, a warning light goes on and the engine stops automatically. If the AC auxiliary power supply is overloaded, a breaker will trip in order to protect the generator.

### 3. Oil Alert System

Equipped oil alert system as standard. It stops engine automatically when oil level has fallen below prescribed level.

### 4. Quiet Operation

Long life DAEDONG Diesel engine is equipped with Large muffler and Large air-cleaner to reduce exhaust noise.

### 5. Easy Operation

Front control panel helps easy operation.

## SPECIFICATION

MODEL		BKS-10000	BKS-13000					
G E N E R A T O R	Phase		1 $\phi$ 3W		3 $\phi$ 4W			
	Frequency	Hz	60	50	60	50		
	Output	Standby / Continuous	11kW/10kW	10kW/9kW	13kW/12kW	11kW/10kW		
	Rated Voltage	V	220/110		380	220	380	220
	Rated Current	A	45.5	40.9	22.8	39.4	19.0	32.8
	Power Factor		1.0		0.8			
	Type		BRUSHLESS					
E N G I N E	Type	DAEDONG 3C093G	RADIATOR WATER-COOLED 4 STROKE, 3 CYLINDER					
	Displacement	cc	927					
	Max Output	kW(ps)	15.4(21)					
	Rated Speed	rpm	3600/3000					
	Fuel		DIESEL					
	Fuel Tank Capacity	ℓ	30					
	Lube Oil Capacity	ℓ	3.8					
	Coolant Capacity	ℓ	6.8					
Battery		12V 45AH x1						
S E T	Dimension(L×W×H)	mm	1350×680×830					
	Dry Weight	kg	335					
	Running Weight	kg	385					
O T H E R S	Indicator		Lamp					
	Emergency Stop	Lube Oil Low Pressure	○					
		Coolant Overheat	○					
		Battery Discharge	○					

 **Koeng Co., Ltd.**

B-806, Twintech Tower, 34 5-9, Gasan-Dong, Geumcheon-gu, Seoul, Korea.  
 TEL: +82-2-838-6300 FAX: +82-2-6292-6292, +82-2-839-4700  
 http://www.koreaeng.co.kr E-mail: export@koreaeng.co.kr

※ The manufacture reserves the right to change the product specifications without notice and liability.