

Soundproof - WELDING GENERATOR

BKW-300sw






WELDING GENERATOR

Perfect Function For Welding Job

SPECIFICATION

MODEL		BKW-300sw			
W E L D E R	Rated Output	Kw	8.74		
	Rated Current	A	280		
	Rated Voltage	V	31.2		
	No-Load Voltage	V	85.0		
	Duty Cycle	%	50		
	Operation		Single	Double	
	Current Range	A	30~300	15~150	
Welding Rod	mm	φ 2.0~6.0	φ 1.6~3.2		
G E N E R A T O R	Phases		3 φ	1 φ	
	Frequency	Hz	60		
	Rated Output	kVA	10	3.0×2	
	Rated Voltage	V	380	220	220
	Rated Current	A	15	16	13.6×2
	Power Factor	%	80	100	
E N G I N E	Type	DAEDONG 3C093G	RADIATOR WATER-COOLED 4 STROKE, 3 CYLINDER		
	Displacement	cc	927		
	Max. Output	kW(ps)	15.4(21)		
	Rated Speed	rpm	3600		
	Fuel		DIESEL		
	Fuel Tank Capacity	ℓ	30		
	Lube Oil Capacity	ℓ	3.8		
	Coolant Capacity	ℓ	6.8		
Battery		12V 45AH×1			
S E T	Dimension(L×W×H)	mm	1350×680×852		
	Dry Weight	kg	385		
	Running Weight	kg	430		
O T H E R S	Welding & A.C. simultaneous use		○		
	Slow-Down		○		
	Emergency Stop	Lube Oil Low Pressure		○	
		Coolant Overheat		○	
		Battery Discharge		○	
	Indicator		Lamp		
Earth Leakage Breaker		Option			

 **Koeng Co., Ltd.**

B-806, Twintech Tower, 34 5-9, Gasan-Dong, Geumcheon-gu, Seoul, Korea.
 TEL: +82-2-838-6300 FAX: +82-2-6292-6292, +82-2-839-4700
 http://www.koreaeng.co.kr E-mail: export@koreaeng.co.kr

※ The manufacture reserves the right to change the product specifications without notice and liability.