






TIRE CHANGER with techno roller (Air jet blast type)



SPECIFICATIONS	KE-3005L
Wheel handled	Alloy 7 Steel & Aluminum
Self-centering claming way	Vane type
Rim size - Inside	560~290mm (24" ~12")
Rim size - Outside	510~240mm (22" ~10")
Max rim width	400mm (15.7")
Max tire diameter	1120mm (44")
Bead breaking power	2140Kg (4700lbs)
Bead breaking distance	340mm (13.3")
Max height	1900mm (74.8")
Max width	1200mm (47.2")
Operation pressure	8~12Bar (116~174psi)
Motor	2Hp
Chuck rotation speed	18rpm
Electrical requirement	1ph, 115V/24A(220V/12A)
Techno-roller Moving range (Up and down)	400mm
Techno-roller applicable size	13" ~ 14"
Techno-roller working air pressure	8~10
Techno-roller cylinder diameter	80mm
Size	1300 x 1888 x 1045mm
Shipping dimension	900(W) * 1120(L) * 900(H)mm
Shipping weight (Net/Gross)	370Kg(816lbs) / 400Kg(883lbs)
Standard accessory	<ul style="list-style-type: none"> ●  Air pressure gauge, ●  Air regulator, ●  Rim lever, ●  Brush, ●  oil barrel

PICTURE OF TECHNO ROLLER PART

